

COLD F.W. WASHING CART

WASH TITAN 200/18/ST



ROBUST CONSTRUCTION

MADE FOR MARINE USE

COMPACT SIZE, WITHOUT MOTOR COUPLING

DIMENSIONS : L550xH600xW620mm - 74kg



- ✓ Female shaft electric motor @ 3ph/1450rpm/1750rpm.
- ✓ Bronze Plunger pump.
- ✓ Ceramic coating pistons.
- ✓ Integrated By-pass valve.
- ✓ Electric Motor thermal protection.
- ✓ Manual pressure regulator.
- ✓ Max inlet water temperature at 65oC.
- ✓ "Total Stop" system, starts and stops the pump automatically by lance trigger operation.
- ✓ Glycerin manometer.
- ✓ Stainless Steel AISI304 frame and protective cover.
- ✓ Four large anti-shock wheels for easy handling.
- ✓ With 900mm lance and gun.
- ✓ With 10m HP hose.
- ✓ With lance and cable holder.



GUN



STANDART EQUIPMENT HP HOSE



LANCE



TECHNICAL SPECIFICATIONS

| Type | Voltage | Power | Pressure | Capacity | Speed | Temp. | Sound level |
|-----------|------------------|-------|------------|----------|--------------|-------|-------------|
| | Volt/Hz | kW | Bar max | Lit/min | rpm | °C | db@3m |
| 200/18/ST | 400/50 440/60 | 5.5 | 200 200 | 15 18 | 1450 1750 | 65 | 70 |

COLD F.W. WATERJET CART

JET TITAN 500/18/ST



ROBUST CONSTRUCTION

MADE FOR MARINE USE

COMPACT SIZE, WITHOUT MOTOR COUPLING

DIMENSIONS : L550xH620xW810mm – 165kg



- ✓ Female shaft electric motor @ 3ph/1450rpm/1750rpm
- ✓ Bronze Plunger pump
- ✓ Ceramic coating pistons.
- ✓ Integrated By-pass valve adjustable by user.
- ✓ Electric Motor thermal protection.
- ✓ Max inlet water temperature at 65°C.
- ✓ Dry running protection at pump suction.
- ✓ "Total Stop" system, starts and stops the pump automatically by lance trigger operation.
- ✓ Electrical Panel with fault indicator lamps.
- ✓ Operation Time (Hours) counter.
- ✓ Glycerin manometer at easily visible point on the front cover.
- ✓ Stainless Steel AISI304 frame and protective cover.
- ✓ Four large anti-shock wheels for easy handling.
- ✓ With 1000mm INOX lance with ceramic nozzle and Quick Release coupling @700bar.
- ✓ With Quick Release gun @600bar.
- ✓ With 10m HP hose, lance and cable holder.
- ✓ Optional equipment (extension HP hoses, special nozzles, shoulder rest) available.

**STANDART
EQUIPMENT**

GUN



**HP
HOSE**



LANCE



TECHNICAL SPECIFICATIONS

| Type | Voltage | Power | Pressure | Capacity | Speed | Temp. | Sound level |
|-----------|------------------|-------|------------|----------|--------------|-------|-------------|
| | Volt/Hz | kW | Bar max | Lit/min | rpm | °C | db@3m |
| 500/18/ST | 400/50 440/60 | 18 | 500 500 | 15 18 | 1450 1750 | 65 | 68 |